




6x25 Filler Wire with
Fiber Core



6x25 Filler Wire with
IWRC



6x26 Warrington Seale
with IWRC



6x19 Seale with IWRC

Size Rope Dia.	Fiber Core (IPS)		IWRC (EIPS)	
	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds
1/4"	.105	5,480	.116	6,800
5/16"	.164	8,520	.18	10,540
3/8"	.236	12,200	.26	15,100
7/16"	.32	16,540	.35	20,400
1/2"	.42	21,400	.46	26,600
9/16"	.53	27,000	.59	33,600
5/8"	.66	33,400	.72	41,200
3/4"	.95	47,600	1.04	58,800
7/8"	1.29	64,400	1.42	79,600
1"	1.68	83,600	1.85	103,400
1.1/8"	2.13	105,200	2.34	130,000
1.1/4"	2.63	129,200	2.89	159,800
1.3/8"	3.18	155,400	3.50	192,000
1.1/2"	3.78	184,000	4.16	228,000
1.5/8"	4.44	214,000	4.88	264,000
1.3/4"	5.15	248,000	5.67	306,000
2"	6.72	320,000	7.39	348,000
2.1/4"	8.51	400,000	9.36	494,000
2.1/2"	10.50	488,000	11.6	604,000
2.3/4"	12.70	584,000	14.0	722,000
3"	15.10	685,000	16.6	850,000